

## DC3 Desktop Charger for Ascom d81 DECT Handset

### Features

- Charging status indicated in handset display
- Handset can be used with full functionality while in charger
- Handset can automatically send absent indication in charger
- Easy to wipe clean



### Technical Specifications

#### Physical

Dimensions (l × w × h):	108 x 95 x 58 mm
Weight:	181 g (excl. power adapter)
Material:	Case: PC/ABS Rubber feet
Colour:	Dark grey

#### Functional

Supply voltage:	100 - 240 V, 50 - 60 Hz AC (adapter), 5 V DC (charger)
Charge current:	0.65 A

#### Environmental

Operating temperature:	+5°C to +40°C
Storage temperature:	-20°C to +65°C
Enclosure protection:	IP30, IEC EN60529
Immunity to electromagnetic fields:	3 V/m EN61000-4-3
Immunity to ESD:	4 kV contact discharge and 8 kV air discharge (EN61000-4-2)

**Compliance to European regulations and standards**

EU directives: 2004/108/EC(EMC)  
Product marking: C E  
Safety: EN60950-1  
EMC: EN 55022 (class B), EN61000-4-3

**Compliance to US regulations and standards**

Product marking:   
Safety: UL 60950-1  
EMC: FCC CFR 47 Part 15

**Compliance to Canadian regulations and standards**

Product marking:   
Safety: CSA 60950-1  
EMC: FCC CFR 47 Part 15

**Compliance to Australian regulations and standards**

Product marking:   
Safety: IEC 60950-1  
EMC: EN 55022 (class B), EN61000-4-3

*Specifications are subject to change without notice.*